

SAVVY EXTERIOR MATT

PRODUCT INFORMATION

Description

A 100% acrylic water thinned paint that dries to a matt finish and is available in white, pastel and deep accent tones. Superior exterior durability - decorates and protects the surface from extreme weather conditions.

Use

This product has excellent opacity using the most light fast pigments for exterior use. Suitable on a variety of substrates such as brick, cement render, masonry, plasterboard, metal and timber. Use on all exterior surfaces in the home and on display and feature sign work when a matt finish is required. It may also be used on all interior surfaces.

Application

Thoroughly stir and apply with brush, roller or spray. Requires two coats for a perfect finish.

Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

Timber – No primer is necessary unless the timber is tannin rich in which case apply Acrylic Wood Primer. Sand and dust down all bare timber and fill holes prior to painting.

Galvanised Iron and Aluminium – Remove oil and grease with mineral turpentine. Apply acrylic metal primer.

Iron and steel – Remove oil, grease and rust. Treat remaining rust with a rust converter then apply acrylic metal primer.

Brick and Masonry – Remove all loose and powdery material with a stiff brush and wash down. No primer required.

Previously painted – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. Spot prime metal with appropriate primer. When using deep tone colours such as Process Yellow and Vip Red apply a white or light grey undercoat first. This will ensure true colour and help coverage.

Drying

Under normal drying conditions (above 15° C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C.

Clean up and thinning

Use clean water only.

Coverage

14 - 16 m² per litre per coat

Pack Size

500 ml, 1 litre 4 litres and 10 litres.

Colours

Colour card and customer specifications.

This technical information and recommendations represent the best information available. They should not be construed as containing any warranty either expressed or implied. Users should conduct their own tests to determine the final suitability. The liability to the company is limited to the replacement of the product, entirely at its discretion.



Atech Solutions Pty Ltd

Unit 10, 632-642 Clayton Road, Clayton South 3169 Australia

PO Box 3215 Mentone East VIC 3194 Australia

Tel: +61 9017 6794 Fax: +61 3 8640 0837

www.atechproducts.com.au