

ALSAN FLASHING

Description: *ALSAN FLASHING* is a waterproofing one-component polyurethane / bitumen resin dedicated to roof waterproofing without flame in new constructions or renovations.

ALSAN FLASHING is ready to use and is applied directly on traditional bituminous waterproofing, without any primer.

Installation: *ALSAN FLASHING* is applied with a brush or roller in 2 or 3 layers on a clean and sound substrate. Mix well the product before usage.

Transitions must be reinforced with *FLASHING REINFORCEMENT*, applied right after the first layer of *ALSAN FLASHING*.

ALSAN FLASHING is UV resistant. It can be left exposed without protection. The top coat can also be covered with roofing granules for aesthetic purposes.

Packaging and consumption:

- 3.78 L and 19 L pails
- Average consumption: 0.75 L/m² per coat
- Storage: Up to 9 months in original sealed containers
- Keep way from any source of heat and dampness

Properties:

Properties	ALSAN FLASHING
Physical state	Brown viscous liquid
Density at 25 °C (g/l)	1070
Solids content (%)	80
Flash point (°C)	2.5
Flammability	Flammable
Minimum Application Temperature (°C)	5 (41 °F)
Drying time	Ready to recoat after 2 hours Dry: 12 hours (remains tacky to touch)

(All values are nominal)

Special indications:

Safety instructions

- Flammable before curing
- Contains isocyanates. Consult Material Safety Data Sheet
- Harmful by inhalation
- Avoid skin contact
- Keep away from sources of ignition – No smoking