

SOPRALENE STICK ADHESIVE

SOPRALENE STICK ADHESIVE is composed of a non-woven polyester and glass grid reinforcement and SBS modified bitumen. A silicone release film covers the self-adhesive under face. The top face is sanded.

SOPRALENE STICK ADHESIVE is a self-adhesive base sheet used over flame sensitive substrates. Most substrates must be primed with **ELASTOCOL 700**.

Available in "Summer Grade" for applications at $T^{\circ} \geq 10^{\circ}C$, and in "Winter Grade" for applications at $10^{\circ}C \geq T^{\circ} \geq -10^{\circ}C$.

For complete information on application and systems, please consult our specification manual.

Properties	Standards	SOPRALENE STICK ADHESIVE
Thickness	-	3.0 mm
Reinforcement	-	Composite heavy duty
Underface	-	Silicone release sheet
Top Face	-	Sanded
Dimension	-	10 x 1 m
Weight	-	35 kg
Storage	-	Upright on pallet
Breaking Strength, MD/XD	ASTM D5147	15 / 13.5 kN/m
Strain Energy, MD/XD	ASTM D5147	7.8 / 7.2 kN/m
Ultimate Elongation, MD/XD	ASTM D5147	60 / 65 %
Cold Bending	ASTM D1970	-30°C
Softening Point	ASTM D36-86	125°C
Static Puncture	ASTM D5602	560 N (120 lb)

(All values are nominal)