

# ATECH PLUS

Flooring Solutions

## UFLOOR® UV MATT

### Non - yellowing Polyurethane Matt Coating

- High Solids
- Low Viscosity
- High Abrasion Resistance
- Fast Cure
- Low Odour

#### Description

UFLOOR® UV MATT is a low solvent based two-component polyurethane based top coat. It provides a matt finish with excellent wear and abrasion resistance and is suited for both indoor and outdoor application.

UFLOOR® UV MATT Parts A and B must be power mixed for at least 5 minutes prior to application.

In order to obtain uniform coverage, UFLOOR® UV MATT should be applied by spray/good quality roller.

Do not apply greater than the recommended coverage, as this might cause cracking and delamination.

#### TYPICAL PROPERTIES

Color	12 Standard Colors
Density	
Parts A & B Pigmented	1.27 Kg/Litre
Parts A & B Clear	1.03 Kg/Litre
Viscosity ( 250°C)	Free Flowing
Mixing Ratio	
By Weight (A:B), Pigmented	5.0 : 1.
By Weight (A:B), Clear	3.33 : 1.

#### Safety Guidelines

Do not use product near flame or open light. Adequate ventilation is required during the application process.

Approved eye protection and gloves are recommended during application.

Should contact occur with eyes or skin, wash thoroughly with soap and water. If irritation persists, obtain medical attention.

Consult Material Safety Data Sheet for details.

#### Consumption

0.150-0.250 Kg/m<sup>2</sup>

#### Packaging

Clear:

Part A = 10 kg pails, Part B = 3 kg units

Pigmented:

Part A = 15 kg pails, Part B = 3 kg units

#### Application Guidelines

The surface to be covered must be clean, dry and free of oil, grease, dirt and any foreign residue. Always apply UFLOOR® UV Matt on primed surfaces for optimum results.

Prime with UFLOOR® GPX, refer to individual datasheet for more information on it's application.

#### Storage

UFLOOR® UV MATT should be kept dry and cool. Shelf life of product stored in original containers is 12 months.

UFLOOR® UV MATT must be protected against moisture.

ATECH SOLUTIONS believes the information herein to be true, accurate and reliable. However, recommendations or suggestions are made without guarantee. Since conditions and disposal are beyond our control, ATECH SOLUTIONS disclaims any liability incurred in connection with the use of our products and information contained herein; no warranty, express or implied is given nor is freedom from any patent owned by ATECH SOLUTIONS others to be inferred.



Atech Solutions Pty Ltd

Unit 10, 632-642 Clayton Road, Clayton South 3169 Australia  
PO Box 3215 Mentone East VIC 3194 Australia  
Tel: +61 9017 6794 Fax: +61 3 8640 0837  
www.atechproducts.com.au

#### Field Support

Field support where provided, does not constitute supervisory responsibility. Suggestions made by ATECH either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they and not ATECH are responsible for carrying out procedures appropriate to a specific application.

#### Customer Responsibility

The technical information and application advice given in this publication is based on the best information available at time of print. As the information herein is of a general nature, no assumption can be made as to the products suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.

#### Safety Precautions

Polyurethane products may cause allergic reactions through skin contact, goggles, protective gloves and overalls must be worn. Ensure that there is adequate ventilation and avoid breathing the vapour.

#### Exclusion Clause

1. The information contained in this data sheet is based on many years experience and is correct to the best of our knowledge. ATECH will be under no liability whatsoever whether in:
  - a) Contract or tort (including, without limitation, negligence)
  - b) Breach of statute
  - c) Any other legal or equitable obligation other than the quality of the product at the time of despatch.
2. Any queries about specification use or application should be directed to our technical service department immediately.
3. This exclusion clause does not operate to exclude any warranty that by law may not be excluded.